



Active V-Groove Alignment

- Heating Time: 13s
- Splicing Time: 4s
- Battery: 3500mAh (up to 200 cycles)



TECHNICAL SPECIFICATIONS

Items	Specifications
Model	i4
Alignment Method	Active V-Groove Alignment
Number of Fibers	Single
Applicable Fibers	SM (G.652 & G.657) / MM (G.651) / DS (G.653) / NZDS (G.655) / CS (G.654) / EDF / BIF
Coating Diameter	100µm - 3mm
Cladding Diameter	80 - 150µm
Cleave Length	5 - 16mm
Typical Splice Loss	SM: 0.03dB / MM: 0.01dB / DS: 0.05dB / NZDS: 0.05dB / G.657: 0.03dB
Return Loss	>> 60dB
Splice Time	Quick mode: Avg. 4 sec / SM mode: Avg. 5sec
Splice Programs	Max 128 modes
Automatic Calibration	Automatic Arc Calibration by air pressure & temperature
Electrode Life span	6000 Arc Discharges
Heating Programs	Max 32 modes
Heating Time	13 sec (45mm, 60mm slim)
Protection Sleeve	20mm - 60mm
Data Output	USB-C
Splice Memory	10,000 Splice data / 10,000 Splice image
Battery	Battery Capacity: 3500 mAh / Operation Cycle: 200 cycles (Splicing + Heating)
Power Supply	AC Input 100 - 240V, DC Input 9 - 19V
Monitor	4.3" Color LCD display, Full Touch Screen
Magnification	x130, x320
Size	132 x 137 x 139mm
Weight	1.384kg (1.164kg without battery)
Pull Test	1.96 - 2.25N

*Splicing Time: Measured from the time of fibers entering the screen until the estimated loss is displayed. Splicing time can vary depending on the calibration status.

*Battery: Measured as 1-minute cycle of splicing and heating. Measured in Power Save mode.


WEIGHT AND DIMENSIONS



ENVIRONMENTAL CONDITION & TEST

Items	Specifications
Operating Conditions	Altitude: 0 - 5000m Humidity: 0 - 95%, non-dew Temperature: -10 - 50°C Wind: up to 15m/sec
Storage Conditions	Humidity: 0 - 95%, non-dew Temperature: -20 - 60°C
Resistance Tests	Shock Resistance : 76cm for bottom surface drop Exposure to Dust : 0.1 to 500µm diameter aluminium silicate Rain Resistance : 10 mm/h for 10 mins

- Water resistance (IPx2)
- Shock resistance (Drop from 76cm)
- Dust resistance (IP5X)



The Information on this catalog is subject to change without prior notice.

i INNO Instrument does not accept responsibility for damages arising from misuse of the product.

For more information, kindly scan the QR code.



SPI ENGINEERS PVT. LTD. (INNO Exclusive Distributor for Sale & Service)

506 & 701, SIDDHARTH BUILDING, 96, NEHRU PLACE, NEW DELHI - 110019 (INDIA)

+91-9717088854, 9818988016, 9810157421

marketing@spiengineers.com

www.spiengineers.com

BRANCHES: Ahmedabad, Bangalore, Delhi, Guwahati, Hyderabad, Indore, Kolkata, Lucknow, Mumbai, Odisha, Hongkong