

A3

BELIEVE YOUR EYES



Made In Korea

A3, CLAD ALIGNMENT ARC FUSION SPLICER

- New Friendly GUI Design
- SOC Support
- 4.3" Color LCD Touch Screen
- Portable Charger Support



DETAILED VIEW I



TECHNICAL SPECIFICATIONS

Specifications	
Model	A3
Alignment Method	Active Clad Alignment (4 Motors)
Number of Fiber	Single
Applicable Fibers	SM (ITU-T G.652&G.657) / MM (ITU-T G.651) / DS (ITU-T G 653) / NZDS (ITU-T G.655)
Coating / Cladding Diameter	Coating Diameter : 100 ~ 3000μm, Cladding Diameter : 80~150μm
Cleaved Length	5 ~ 16mm
Typical Splice Loss	SM: 0.03dB / MM: 0.01dB / DS: 0.05dB / NZDS: 0.05dB / G.657: 0.03dB (Measured by fusion splicing compensating cutback according to ITU-T standard)
Return Loss	>> 60dB
Estimated Splice Loss	Available
Splice Time	Quick mode 7s
Splice Mode	Preset 6 kinds of splicing mode, Max 320 mode available
Heating Sleeve	20 ~ 60mm
Heating Time	15s (45mm, slim 60mm), 20s (60mm)
Heating Mode	Max 32modes
Pull Test	1.96 ~ 2.25N
Dimension	197W x 137D x 87H mm (including rubber bumper) / 187W x 128D x 82H mm (excluding rubber bumper)
Weight	1.206kg (with battery) / 0.997kg (without battery)
White LED	2 White LEDs
Monitor	4.3" Color LCD display, Full touch screen
Fiber View	X, Y, X/Y
Magnification	120 ~ 240x
Results Storage	10,000 Splice data / 10,000 Splice image
Power Supply	AC Input 100 ~ 240V, DC Input 9 ~ 14V
Terminal	USB Type C
Battery Capacity	3000mAh Battery Capacity, Typical 150 cycles (Splice+Heat), Power save mode 200 cycles (Splice+Heat)
Electrode Life	5500 arcs discharges

PACKAGE LIST Standard Package

Model / Part No.	Description	
A3	Main Unit	
	Fusion Splicer	
	Standard Accessories	
	V7	Cleaver 1ea
	FH-45	Fiber Holder 1set
	FH-SOC-L	SOC Fiber Holder 1ea
	HTS-SOC-05	SOC Heater Cover 1ea
	JS-1618	AC Adapter 1ea
	CG-22	Cooling Tray 1ea
	E-50	Electrode 1set
	LBT-3000-02	Battery Pack (3000mAh) 1ea
	ACC-25	Power Cable 1ea
	USB-8P	USB Cable 1ea
	USB-9P	USB Cable 1ea
	ICC-54	Carrying case 1ea
	IWS-05	Work Station for A2, A3 1ea
	ST-01	Shoulder Strap (Carrying Case) 2ea
		Quick Reference 1ea

*USB-8P Type-C USB to Type-A USB (Male) Cable
*USB-9P Type-C USB to Type-A USB (Female) Cable

The Information on this catalog is subject to change without prior notice.



SPI ENGINEERS PVT. LTD. (INNO Exclusive Distributor for Sale & Service)

506 & 701, SIDDHARTH BUILDING, 96, NEHRU PLACE, NEW DELHI - 110019 (INDIA)

+91-9717088854, 9818988016, 9810157421

www.spiengineers.com

marketing@spiengineers.com

BRANCHES: Ahmedabad, Bangalore, Delhi, Guwahati, Hyderabad, Indore, Kolkata, Lucknow, Mumbai, Odisha, Hongkong

PACKAGE LIST Optional Accessories

Model / Part No.	Description	
TK02-AP01	Alcohol Pump	1 ea
TK02-MP01	Stripper	1 ea
EG-18	Electrode Grinder	1 ea
PS-60S	Heating Sleeve (60mm)	1 pack (100ea)

ENVIRONMENTAL CONDITION & TEST

Items	Specifications
Operating Condition	Altitude: 0 ~ 5000m Humidity: 0 ~ 95%, non-dew Temperature: -10 ~ 50 °C Wind: up to 15m/sec
Storage Condition	Humidity: 0 ~ 95%, non-dew Temperature: -20 ~ 60 °C
Resistance Tests	Shock Resistance : 76cm for bottom surface drop Exposure to Dust : 0.1 to 500um diameter alu-minium silicate Rain Resistance : 10 mm/h for 10 mins

- Water resistance (IPx2)
- Shock resistance (Drop trom 76cm)
- Dust resistance (IP5X)



* We do no guarantee and are not responsible for any damage caused due to tampering of the product under above conditions.